



STANDARD TURBIDITY BARRIER COMPONENTS

TYPE	FABRIC WEIGHT	FOAM	MAXIMUM DEPTH	CHAIN	CABLE	ROPE YELLOW	GROMMET	HARDWARE	FILTER FABRIC
1.DOT	18 OZ <small>(22 OZ AVAILABLE UPON REQUEST)</small>	6" UP TO 20'	50'	1/4"	NO	5/8"	#4	NO	NO
		8" OVER 20'							
2.DOT	18 OZ <small>(22 OZ AVAILABLE UPON REQUEST)</small>	8" UP TO 20'	100'	5/16" UP TO 59'	5/16"	5/8"	#5	STANDARD [†]	NO
		10" OVER 20'		3/8" OVER 59'					
		12" OVER 39'							
3.DOT	18 OZ <small>(22 OZ AVAILABLE UPON REQUEST)</small>	8" UP TO 20'	100'	5/16" UP TO 59'	5/16"	5/8"	#5	STANDARD [†]	FW700
		10" OVER 20'		3/8" OVER 59'					
		12" OVER 39'							
1.m	18 OZ	4"	20'	1/4"	NO	3/8"	#4	DRAIN HOLES	NO
2.m	18 OZ	4" UP TO 10'	20'	1/4"	1/4"	3/8"	#4	NO 3/8" SHACKLE / +1-5/16" SHACKLE	NO
		6" OVER 10'							
3.m	18 OZ	4" UP TO 10'	20'	1/4"	1/4"	3/8"	#4	NO 3/8" SHACKLE / +1-5/16" SHACKLE	FW700
		6" OVER 10'							

[†]Standard Hardware: 4-BARS, 4-CORNER PLATES, 4-5/16" SLEEVES, 2-5/16" THIMBLES, 4-5/16" SHACKLES, 1-3/8" SHACKLE