



TOUGH-GUY® FLOATING TURBIDITY BARRIER

TYPE 1.DOT SPECIFICATIONS

Fabric: 18oz. nominal PVC coated polyester	
Base Fabric (100% Polyester)	1000Dx1000D / 9x9
Weight (FS-191-5041)	18oz./yard ²
Tensile Strength, Grab (ASTM 4632)	325 lbs x 310 lbs
Tear Strength, Tongue (ASTM 2261)	55 lbs x 45 lbs
Elongation (ASTM 4632)	21% x 21%
Adhesion Strength (ASTM 751)	17x17 lbs/inch
Abrasion Resistance (ASTM 4833)	325 cycles
Hydrostatic Resistance (ASTM 751)	At least 660 lbs/inch ²
UV Resistance (Weather-O-Meter)	Not excessive fading after 1000 HRS
Cold Crack Resistance (ASTM 2136)	-40°F
High Temperature Resistance (ASTM 2136)	180°F (Does not Block)
Flame Resistance	Pass
Special Treatment(s)	Anti Mildew



All seam heat sealed

5/8" diameter poly rope reinforced vertical edges

#4 brass grommets

1/4" galvanized chain ballast

EPS flotation foam: 6" x 6", 13.5 lb./ft. buoyancy in fresh water and 14.4 lb./ft. buoyancy in saltwater

MADE IN THE USA

SOLD ONLY BY AER-FLO DISTRIBUTORS

PH: 800.823.7356 | FX: 941.747.5489 | info@aerflo.com | AerFlo.com