



BARRIER ACCESSORIES

ANCHOR KITS

The Tough Guy® Anchor Kit includes everything needed to anchor Tough Guy® Floating Turbidity Barriers — anchor, rope, chain, shackles, thimbles, anchor buoy, and positioning/retrieval buoy and the inflation needle used to inflate the two buoys.

All of these anchoring system elements are factory assembled and make jobsite installation easy. At the jobsite, a snap onto the cable loop at the end of the turbidity barrier's top load cable is all that is required.

Kit A - 18-pound anchor | Kit B - 25-pound anchor

Both kits include 50 feet of rope to use in water depths of up to 10 feet. For deeper waters, longer rope can be added as an option. Kits are easy to install: just snap onto cable loop at joint of turbidity barrier's top load line; position, reposition, and remove with positioning/retrieval buoy.

LIGHTED NAVIGATION BUOYS

Lighted navigation buoys are required by the Coast Guard for floating turbidity barriers in navigable waterways.

We developed our line of lighted buoys to work for a wide range of projects and in across a variety of uses.

Our specially-designed unit is ultra-stable in rough waters due to underwater counter ballast weight sealed inside PVC pipe and water level attachment. The floatation unit is sealed with styrene foam.

We developed this line of buoys as a value-priced alternative to the more costly units in the marketplace.

Aer-Flo, Inc's Lighted Navigation Buoys meet or exceed the U.S Coast Guards recommendation for Floating Turbidity Barriers. Due to the proprietary nature of this product, please call Aer-Flo Customer Service for additional information: **(833) 818-1563**.



ANCHOR KIT SPECS

- Standard length is 50'
- Standard depths are 3', 5', and 10'
- Standard color is Tough Guy® Yellow.
- Custom colors are available.

LIGHTED BUOY FEATURES

- Replaceable, automatic photocell night-on/day-off, high intensity while flashing light positioned on top of the buoy
- Light has 3-mile visibility
- Initial battery life will extend up to 18-months
- Signal light meets the 39" above-water height regulation requirement



SOLD ONLY BY AER-FLO DISTRIBUTORS

PH: 833.818.1563 | FX: 941.747.5489 | AerFloEnv.com