



# STAKED BARRIER

## SPECIFICATIONS FOR STAKED BARRIER WITH 18 OZ. FABRIC

	English	Metric	Testing Method
Weight	18 oz/yd <sup>2</sup>	610g/m <sup>2</sup>	FS 5040/ASTM D3776
Standard Dimensions	44.5 in. high x 100 ft	1.13m high x 30.5m	
Construction	9 x 9/1 by 840x840	4 x 4 / cm by 924 x 924	
Grab Tensile	281 x 247 lbs. / 2"	1250 x 1100 N / 5 cm	FS 5100 / ASTM D5034
Tongue Tear	51 x 45 lbs. / 1"	225 x 200 N / 2.5 cm	FS 5134 / ASTM D2261
Adhesion	20 lbs. / 2"	90 N / 5 cm	FS 5970 / ASTM D751
Finish	Matte	Matte	
Cold Crack	-4° F	-20°C	FS 5874 / ASTM D2136
Fire Retardent	Self Extinguishing	Self Extinguishing	PASS

All seams heat sealed

Stakes are not included

**Standard size:** 100 ft in length x 44.5 inches

MADE IN THE USA

SOLD ONLY BY AER-FLO DISTRIBUTORS

PH: 941.747.4151 | FX: 941.747.5489 | AerFloEnv.com