



TOUGH-GUY FLOATING BAFFLE CURTAIN SPECIFICATIONS

Fabric:	18oz. standard, 22oz. & 30oz. available
Base Fabric (100% Polyester)	1000D x 1000D / 9 x 9
Weight (FS-191-5041)	18oz./yard ²
Tensile Strength, Grab (ASTM 4632)	325 lbs x 310 lbs
Tear Strength, Tongue (ASTM 2261)	55 lbs x 45 lbs
Elongation (ASTM 4632)	21% x 21%
Adhesion Strength (ASTM 751)	17 x 17 lbs/inch
Abrasion Resistance (ASTM 4833)	325 cycles
Hydrostatic Resistance (ASTM 751)	At least 660 lbs/inch ²
UV Resistance (Weather-O-Meter)	Not excessive fading after 1000 HRS
Cold Crack Resistance (ASTM 2136)	-40°F
High Temperature Resistance (ASTM 2136)	180°F (Does not Block)
Flame Resistance	Pass
Special Treatment(s)	Anti Mildew



All seams heat sealed

5/8" diameter poly rope reinforced vertical edges

#5 brass grommets

Optional 5/16" or 3/8" top loading cable available

1/4" galvanized chain ballast, 5/16" & 3/8" available

Aluminum stress plates at cable and chain terminations for baffle curtains with cables

EPS flotation foam: 6" standard, 8", 10", & 12" available

Optional Universal End Connectors available

MADE IN THE USA

SOLD ONLY BY AER-FLO DISTRIBUTORS

PH: 941.747.4151 | AerFloEnv.com